

SEFAR® BASIC		vazba		velikost oka	jmenovitý průměr vlákna	stupeň otevřenosti síta	tloušťka síťoviny	teoretický objem barvy	dodávané šíře								
označení - cm/palec				µm	µm	%	µm	cm³ / m²	cm palec	115 45	142 56	158 62	186 73	234 92	288 113	320 124	365 143
32/83-100W		PW	1:1	209	100	45	163	73			x	x					
34/85-100W		PW	1:1	190	100	42	163	68			x						o
36/92-90W		PW	1:1	183	90	43	144	62			x	x					
43/110-80W		PW	1:1	149	80	41	130	53		x	x	x		x		o	
43/110-80Y		PW	1:1	149	80	41	130	53			x	o					
48/123-70W		PW	1:1	135	70	41	111	47		x	x	x					
51/131-70W		PW	1:1	121	70	38	109	42				x					
54/137-64W		PW	1:1	118	64	39	98	40		x	x	x		o		x	
54/137-64Y		PW	1:1	118	64	39	98	40				x					
61/156-64W		PW	1:1	97	64	30	100	35		x	x	x		x	x	x	
61/156-64Y		PW	1:1	97	64	30	100	35			x	x					
68/175-55W		PW	1:1	84	55	33	84	27				x					

SEFAR® BASIC		vazba		velikost oka	jmenovitý průměr vlákna	stupeň otevřenosti síta	tloušťka síťoviny	teoretický objem barvy	SERVIS CENTRUM 								
označení - cm/palec				μm	μm	%	μm	cm³ / m²	cm palec	115 45	142 56	158 62	186 73	234 92	288 113	320 124	365 143
68/175-55Y		PW	1:1	84	55	33	84	27				x					
68/175-64W		PW	1:1	78	64	28	98	28								o	
71/180-55W		PW	1:1	78	55	36	86	26		o	x	x		o			
71/180-55Y		PW	1:1	78	55	36	86	26				o*					
77/195-48W		PW	1:1	77	48	35	78	27				x					
77/195-48Y		PW	1:1	77	48	35	78	27				x					
77/195-55W		PW	1:1	67	55	26	84	22		x	x	x	o	x	o	x	x
77/195-55Y		PW	1:1	67	55	26	84	22		x	x	x		x			
90/230-48W		PW	1:1	55	48	25	75	18		x	x	x	o	x			
90/230-48Y		PW	1:1	55	48	25	75	18		x	x	x		x		o	
100/255-40W		PW	1:1	57	40	32	62	20		x	x	x	o			o	
100/255-40Y		PW	1:1	57	40	32	62	20		x	x	x		x			

SEFAR® BASIC		vazba		velikost oka	jmenovitý průměr vlákna	stupeň otevřenosti síta	tloušťka síťoviny	teoretický objem barvy	SERVIS CENTRUM 								
dodávané šíře																	
označení - cm/palec			μm	μm	%	μm	cm ³ / m ²	cm palec	115 45	142 56	158 62	186 73	234 92	288 113	320 124	365 143	
110/280-40Y	PW	1:1	47	40	27	63	17				x						
120/305-34W	PW	1:1	45	34	30	52	15		x	x	x		o		o		
120/305-34Y	PW	1:1	45	34	30	52	15		x	x	x		x				
120/305-40W	PW	1:1	37	40	20	62	12		o		x						
120/305-40Y	PW	1:1	37	40	20	62	12						o		o		

podmínky objednání u dodavatele:

x – skladem v SC, termín dodání 1-2 dny

x – skladem v SEFARU, termín dodání 1-2 týdny, objednávka podmíněna minimálním množstvím (1 role cca 25 bm)

o – objednávka na dotaz, objednávka podmíněna minimálním množstvím (1 role cca 25 bm)

* také v šíři 160 cm